

Best practice and quality assessment procedures for site characterization at seismic station: an European initiative

Cultrera Giovanna¹, Di Giulio Giuseppe¹, Cornou Cécile², Bard Pierre-yves², and Al Tfaily Bilal²

¹Istituto Nazionale di Geofisica e Vulcanologia

²Univ. Grenoble Alpes, Univ. Savoie Mont Blanc, CNRS, IRD, IFSTTAR, ISTerre

November 16, 2022

Abstract

Seismic site characterization of rock and soil properties has a large impact on earthquake ground motions and engineering seismology, especially for evaluation of local site amplification, calibration of strong-motion records and realistic shaking estimates at seismic stations, site-specific hazard assessment, estimation of ground motion models and soil classification for building code applications. However, there is not yet a common way to exchange site characterization information, whereas setting-up standard practices and quality assessment are becoming very important to reach high-level metadata. Within the framework of the SERA “Seismology and Earthquake Engineering Research Infrastructure Alliance for Europe” Horizon 2020 Project, a networking activity is leading to the definition of a European strategy and standards for site characterization of seismic stations in Europe. Based on the results of an online questionnaire, we first defined a list of indicators considered as mandatory for a reliable site characterization: fundamental resonance frequency, shear-wave velocity profile (V_s), time-averaged V_s over the first 30 m, depth of seismological and engineering bedrock, surface geology, soil class. We then proposed a summary report for each indicator, containing the most significant background information of data acquisition and processing details, and a quality metrics scheme. This requires the evaluation of both (i) reliability of the site characterization indicators provided by different methods, and (ii) consistency among the indicators according to the current knowledge and experience of the scientific community. The quality metrics application to some Italian accelerometric sites, characterized within the Italian Civil Protection Department-INGV agreement (2016 to 2021), highlights the capabilities of capturing the characterization quality. These guidelines have been shared within European and worldwide scientific community and validated through focus groups during a dedicated workshop (<https://sites.google.com/view/site-characterization-workshop/>). They represent a first attempt to reach high-level metadata for site characterization, being aware that they can be improved and modified after a few years of experience and feedback from users.

Giovanna Cultrera¹, Giuseppe Di Giulio¹, Cécile Cornou², Pierre-Yves Bard², Bilal Al Tfiaily²

¹ Istituto Nazionale di Geofisica e Vulcanologia - INGV (Italy)

² ISTERre, Univ. Grenoble Alpes, Univ. Savoie Mont-Blanc, CNRS, IRD, IFSTTAR (France)

giovanna.cultrera@ingv.it

1 Introduction

Seismic site characterization of soil properties at seismic stations has a large impact on earthquake ground motions and engineering seismology, especially for evaluation of local site amplification, calibration of strong-motion records and realistic shaking estimates, site-specific hazard assessment, estimation of ground motion models and soil classification for building code applications.

In recent years, the number of stations of permanent seismic networks worldwide is largely increased, rising the amount of earthquake signals and the applications using real-time recordings.

European Integrated Data Archive EIDA
<https://www.orfeus-eu.org/data/eida/>

However, there is not yet a common way to exchange site characterization information, whereas setting-up standard practices and quality assessment are becoming very important to reach high-level metadata.

Site Class	Inferred (geology and/or slope)	Other
A	253	74
B	466	213
C	254	158
D	10	8
E	3	16

Engineering Strong Motion (ESM) database (<http://esm.mi.ingv.it>; Luzi et al. 2016): distribution of strong motion stations as a function of EC8 site categories (CEN 2004). Out of 2071 permanent seismic stations, 70% have an EC8 soil class, but only 22% have a Vs30 measured with different methods. From Lanzano et al. (2019).

Within the framework of the SERA "Seismology and Earthquake Engineering Research Infrastructure Alliance for Europe" Horizon 2020 Project, a networking activity is leading to the definition of a European strategy and standards for site characterization of seismic stations in Europe (SERA-NA5, lead by C. Cornou). The standards, proposed by Task2 "Best practice and site characterization quality assessment", have been shared within European and worldwide scientific community and validated through focus groups during a dedicated workshop (<https://sites.google.com/view/site-characterization-workshop/>). They represent a first attempt to reach high-level metadata for site characterization, being aware that they can be improved and modified after a few years of experience and feedback from users.

2 A voting Questionnaire for consensus

Following a preliminary investigation, we defined a list of indicators for site effect characterization, for which we asked the opinion of a broad audience coming from different scientific fields. The investigation was carried out through an online Questionnaire sent to more than 300 colleagues on different scientific fields.

Answers from 71 team/researchers from different countries (69% Europe, 31% other countries)

different scientific fields (seismology, geophysics, geotechnical engineering, etc.)

Scientific field: Seismology, Geophysics, Geotechnical Engineering, Engineering, Geology, etc.

What we asked

We proposed a list of indicators for which we asked:

- the best method of estimation
- the feasibility index (level of difficulty for deriving it) → data acquisition and method of analysis
- the cost for deriving it

Importance

Indicators list

- f_0, f_1, \dots, f_n and A_0, A_1, \dots, A_n
- Site Transfer Function (STF)
- Preferential direction of ground motion
- Duration Lengthening
- $kappa_0$
- Frequency-dependent attenuation
- V_{s30} , V_{s2} , V_{s1} , V_{s0}
- Vs and H of seismic bedrock
- H_{eng_bed} , $V_{eng}(z)$, $V_s(z)$
- dispersion curve, Rayleigh wave ellipticity
- Building code Site Class (soil class)
- Aggravation factor for basin and topography
- Surface geology
- Topographic factor, Geometrical parameter
- geo-stratigraphic 1D log model
- H_{water_table}
- Non-linear degradation curves
- Geotechnical parameter

3 Most recommended indicators

The results of the online questionnaire led to a list of indicators considered as mandatory or at least most recommended for a reliable site characterization and that should be available in strong motion databases.

Mandatory parameters > 50% of answers

- The majority of indicators are recommended for a reliable site characterization
- few of them are largely considered as mandatory:
 - fundamental resonance frequency (f_0),
 - average shear-wave velocity V_S in the first 30 m of depth (V_{S30}),
 - seismic bedrock depth,
 - engineering bedrock depth (corresponding to a V_S fixed in the Building code),
 - Subsoil velocity profile of shear-wave as a function of the depth ($V_S(z)$),
 - site class according to a specific Seismic Building Code,
 - Geological and lithological information from available cartography and/or geological surveys
- Missing important parameters (12% YES):
 - 1D/2D/3D effects, Uncertainties, Dependence to the earthquake location

4 Results

For each indicator, different data type/processing are chosen and, for each selection, 3 levels of feasibility (easy, intermediate and difficult) and 3 levels of cost (small, intermediate and high). For example, the best data acquisition and processing methods to compute f_0 uses noise and earthquake data: it is easier to compute it from noise and less expensive.

For each indicators, both the average difficulty index and cost index are computed by weighting the individual feasibility and cost obtained for each method, scooting to the number of people recommending each method:

- the higher is the difficulty to infer the indicator, the larger is the cost;
- the most recommended indicators (orange) do not depend on cost or difficulty: the choice is related to the confidence on them.

Size is proportional to number of recommendation for mandatory

5 Summary report

We then proposed a summary report for each recommended indicator, containing the most significant background information of data acquisition and processing details.

Complete reports → Summary report → Databases (indicator's value)

Content:

- General:** Authors, Contacts, Link to reports, papers; Coordinates of the site
- Data acquisition:** Date of experiment, Location, Equipment, Instrumental setting
- Data analysis (processing methods and parameter s):** Methodology and general processing parameters, Results, Uncertainties and limits of resolution
- Result:** Average estimate and standard deviation

Example of summary report for f_0

6 Quality metrics

There is a need for an overall quality metrics to define level of reliability of the site characterization, to be included in seismic station metadata. This requires the evaluation of both (i) reliability of the indicators provided by different methods, and (ii) consistency among them, according to the current knowledge and experience of the scientific community:

$$Final_Q_{index} = \frac{Q_{index2}(Q_{index1}) + Q_{index3}}{2} [0 \div 1]$$

Index 1: Quality of single indicator

$$Q_{index1} = \frac{[(a + b * c) * d]}{a_{max} + b_{max} * c_{max}} [0 \div 1]$$

(a) Method of acquisition and analysis; (b) Direct measurement / inferred value; (c) processing; (d) Completeness of the report (If no report then = 0 !)

Definition	Value	Explanation
a) Method of acquisition and analysis	1	peer-reviewed papers
	0	not published
b) Estimation of indicator	2	field experiments
	0	inferred values
	0.5	partial confidence
	0	incorrect
c) Processing	1	robust
	0.5	partial confidence
	0	incorrect
d) Completeness of the report	1	well-documented
	0.5	Incomplete
	0	Not available

7 Index 2: Quality of an overall characterization

Weighted sum on Q_{index1} of $n=7$ most appropriate indicators:

$$Q_{index2} = \frac{\sum_{i=1}^n [w_i * Q_{index1}^i]}{\sum_{i=1}^n w_i} [0 \div 1]$$

Weight is maximum for direct measurements indicator

Indicator	Value
f_0	1
$V_S(z)$	1
V_{S30}	0.5
H_{seis_bed}	0.5
H_{eng_bed}	0.5
geology	0.5
soil_class	0.25

8 Index 3: Consistency of results

Quantification of the overall compatibility between the various indicator's value:

$$Q_{index3} = \frac{\sum_{k=1}^m cons(k)}{m} [0 \div 1]$$

Where $cons(k)=1$ if consistent, 0 if not consistent, and $m=5$ is the number of available couples of indicators for which published relationships references are available:

- $k=1$ (f_0 & V_{S30})
- $k=2$ (f_0 & seismic bed. depth)
- $k=3$ (f_0 & engineering bed depth)
- $k=4$ (V_{S30} & engineering bed. depth)
- $k=5$ (V_{S30} & geology)

The consistency can be assessed in case-study papers focused on deriving a specific indicator or through empirical relationships between various indicators. However, when there are not available studies, or in addition to, we propose a reference set of scatter plots to compare with the measured value at a specific site.

Scatter plot for couple of indicators: a) f_0 - seismic bedrock depth ($H_{bedrock}$ in m), b) f_0 - V_{S30} (in m/s). Red: simulated values; others: real values from selected Italian sites.

- We select 935 strong motion sites where real V_S profiles are available (602 Kiknet, 243 Californian, 21 European strong-motion, 33 French and 36 Italian).
- The indicators, except for V_S , are computed by using a 1D velocity model and processing homogeneously the resulting data: V_{S30} site class, depth of engineering bedrock (H_{300}) and f_0 from the SH amplification (reflectivity method; Kennet, 1983); seismic bedrock depth for which the resonance frequency provided by the Rayleigh's method is similar to the measured f_0 .

9 Examples

The quality metrics of some Italian accelerometric sites highlights the capabilities of capturing the characterization quality.

The information on the site characterization are available at the Italian Accelerometric Archive (ITACA; <http://itaca.mi.ingv.it>).

The IV sites were studied in the framework of a project for site characterization of permanent Accelerometric Italian Networks (Italian Civil Protection Department, DPC, and INGV agreement 2012-2021 All. B2 Task B; Cultrera et al. 2018).

- CDCA and ORC: all the recommended indicators are well computed ($Q_{index1}=1$) but the measured values at ORC do not fit the scatter plot ($Q_{final}=0.7$);
- ROM9: as CDCA but V_S values from different methods are not consistent because of possible processing problem (lower $Q_{final}=0.8$);
- MCA and CSM: few indicators available, for none of them it is possible to assess consistency; Q_{final} is higher at MCA because of 3 indicators including f_0 .